


## WIRE MANAGEMENT SYSTEM **BLA+ DOUBLE HANGER**

## ABOUT

The CableSmart<sup>™</sup> Double Hanger, as part of the wire management system, allows you to suspend power and data cables above ground negating the need to dig costly trenches. With a capacity of up to 1170 6 mm<sup>2</sup> (0.2 in<sup>2</sup>) cables, the hanger is ideal for routing cables on larger scale projects and can be stacked as part of a modular system to further improve system capacity.




A 216 mm / 8.5 in

- B 218 mm / 8.6 in
- 75 mm / 3.0 in С 160 mm / 6.3 in D
- E 35 mm / 1.4 in
- F 6 mm / 0.2 in
- G 120 mm<sup>2</sup> / 4.7 in<sup>2</sup>
- H 10 mm / 0.4 in
- I Polycarbonate UV Stabilized
- J 2 mm / 0.1 in G90 Steel



Messenger Grip Quick to install



Modular Hook Additional capacity



Swing Gate

Easy to secure

UV Resistant

Built to last

Side Loading Fast cable loading



Data Holder Data expansion



Steel Plate Strong reinforcement



Slim Profile Easy to handle

PERFORMANCE	SUPPLY	PROPERTIES	CABLE CAPACITY
Load Rating: 30 kg / 66 lbs	Part Number WMS00005	Thickness: 20 mm / 0.8 in	750 MCM ≈ 22
Design Life: +30 years	Unit Weight: 0.29 kg / 0.6 lbs	Colour: Black	250 MCM ≈ 48
	Box Quantity: 36	Stackable: Yes	<b>4/0</b> ≈ 70
	Pallet Quantity: 864		10 mm² / 0.4 in² (8 AWG) ≈ 588
	Pallet Weight: 375 kg / 827 lbs		6 mm² / 0.2 in² (10 AWG) ≈ 1170
			4 mm² / 0.16 in² (12 AWG) ≈ 1460

