

WIRE MANAGEMENT SYSTEM MESSENGER WIRE HANGERS

ABOUT

The Shoals Wire Management System introduces a new level of organization to your solar installation. Proper routing and wire management eliminates abrasion, tension, and stress points that contribute to early failures and costly downtime. The Shoals Wire Management System removes waste from the site and ends the use of zip ties. The simplified design and robust construction also increases reliability while decreasing O&M costs. This makes it the perfect solution for any project.

FEATURES

- For use outdoors
- Simple to install
- UV/sunlight resistant
- Improves project aesthetics
- Stainless steel reinforced thermoplastic
- Separate sections for source circuit wires
- Standard 5-year warranty on all models
- Works with all messenger wire systems
- ETL certified to UL1565
- Patent Pending



STG.WMS.MH1



STG.WMS.MH2



STG.WMS.MH3



STG.WMS.MH4



STG.WMS.MH4
example wire layout

TECHNICAL SPECS	STG.WMS.MH1	STG.WMS.MH2	STG.WMS.MH3	STG.WMS.MH4
Application Type	Messenger wire hanger			
Messenger Wire Types	Copper or steel, bare 4AWG maximum diameter			
No. of 750kcmil BLA Wires ^(a)	2	2	2	2
No. of 750kcmil DC Feeder Wires ^(a)	0	2	4	6
No. of Source Circuit Wires ^(b)	up to 4	up to 4	up to 6	up to 8
Operating Temp. Range	-40 to 90°C			

(a) Smaller BLA or DC feeder wire sizes may allow higher quantity of wires

(b) 10AWG or 8AWG typical

Product design and specification subject to change or modification without notice.

